


1310/1550NM WDM

Description

Fused Biconic Taper (FBT) Technique is used to make our single mode wavelength division multiplexers (WDM). The WDM multiplexes two optical carrier signals signals at 1310nm and 1550nm wavelengths on a single optical fiber to carry different signals, or de-multiplexes the signals from a single fiber into two separate fibers. This allows for a multiplication in capacity, in addition to making it possible to perform bi-directional communications over one strand of fiber. The true potential of optical fiber is fully exploited when multiple beams of light at



different frequencies are transmitted on the same fiber.

Our WDM products have low polarization dependence. In addition to standard WDM (isolation \leq 20dB), we also provide HWDM (isolation \leq 38dB) and SWDM (isolation \leq 45dB).

Features

- Low insertion loss
- High wavelength isolation
- Low polarization dependence
- Environmentally stable

Applications

- WDM Networks
- CATV

Specifications

Characteristics	Unit	Value/Performance		
Center Wavelength	nm	1310 and 1550		
Bandwidth	nm	<u>+</u> 10		
Insertion Loss	dB	≤0.15 (0.1 typ.)		
Isolation	dB	≥20		
Polarization Dependent Loss	dB	≤0.1		
Thermal Stability	dB/°C	≤0.002 over -40 ~ +80°C		
Directivity	dB	≥60		
Configuration	-	1x2 or 2x2		
Lead Length	m	1, others on request		
Lead Type	-	250um bare fiber	900um loose tube	2 or 3mm loose tube
Package Type	-	A1	A3 or B	B or C
Operating Temperature	°C	-40 ~ +80	-20 ~ +70	-20 ~ +70

Dimensional Drawing

Please see coupler package information.

Ordering Information

Part Number: WDM-12 3 SM 1 A1- 1 SA

1 2

3 4 5 6

Configuration 12=1x2, 22=2x2

2 Wavelength 3=1310nm & 1550nm

3 Lead Type 1=250um, 2=900um, 3=2.0mm, 4=3.0mm

4 Package Type A1, A3, B or C

5 Lead Length 0.5=0.5m, 1=1m, etc.

6 Connectors Terminated Blank=no connector, FU=FC/UPC, FA=FC/APC, SU=SC/UPC,

SA=SC/APC

Products manufactured in ISO 9001 certified facilities



